



## Audiocups Noise-reducing enclosures

Industry-leading audiometric enclosures, designed to assist with accurate pure tone hearing screening in conditions where ambient noise is too high for unshielded earphones.

#### Considered design

Incorporating a fully articulated earphone suspension system ensures earphone cushions are able to locate against pinnas of all shapes.

While at the same time audiocup cushions enclose the external ear to exclude background noise.

#### Performance

These noise-reducing enclosures are designed to provide unique noise attenuation to assist in accurate audiometry measurements when compared to standard audiometry headsets.

Audiometry threshold measurements should be recorded in accordance to the maximum stated ambient noise levels advised in ISO 8253-1:2010.

#### The perfect add-on

Our Audiocups are the perfect add-on to a standard air conduction headset such as the RadioEar DD45, Telephonics TDH39 and TDH49 transducer.

Easily retrofitted in the field without the need for recalibrating your audiometer.

#### Key features

Industry leading attenuation, designed to minimise external noise

Suitable for environments where ambient noise may affect test accuracy

Lightweight, adjustable and ergonomically designed for an accurate and comfortable fit

Articulated suspension of the earphone provides an accurate and comfortable fit

Easily fitted to any RadioEar DD45, Telephonics TDH39 and TDH49 type earphone

No requirement to recalibrate after fitting

Please note: image shows complete headset with fitted transducers.



### Audiocups

Noise-reducing enclosures

#### Attenuation

The attenuation provided using TDH39 earphone with MX41/AR ear cushions within an audiocup headset is shown below:

Frequency Hz	Attenuation dB	Deviation dB
125	9	6
250	13	6
500	24	8
1000	30	8
1500	32	7
2000	39	7
3000	44	5
4000	44	8
6000	44	10
8000	35	7

#### Dimensions

Material:	Moulded ABS plastic	
Weight:	350g / 0.77lbs	

Audiocups can be supplied as noise-reducing enclosures to fit existing earphones or as a complete headset with fitted transducers, cushions and headset lead.

The addition of Audiocups to your existing headset will not impact the calibration of your audiometer. A re-calibration of your audiometer is not required.

#### Standard equipment

 Headband, headband cover and red and blue ear shells with outer ear cushion

#### **Optional equipment**

- Headset lead
- TDH39 or DD45 earphones with inner ear cushion
- Screwdriver set
- Disposable large ear cushion covers



Please note: These parts can be supplied with Audiocups at an additional cost for the assembly of a full headset. A calibration will need to be completed for the new headset and audiometer.

#### Compatibility

Suppliers:	Interacoustics, MAICO Diagnostics, Inventis, Resonance, Tremetrics, Minato, Inission, Sibel, Natus, Neurosoft, Opportunities, Beijing BTBD, Sivantos, Idem and Auditdata
Products:	All Amplivox audiometers, AD226 from Interacoustics, MA25 from MAICO, Bell and Piccolo from Inventis, r07a and R27A from Resonance, RA300 and RA660 from Tremetrics, Neuro-Audio/PTA from Neurosoft, Sibelsound Duo from Sibel and the SD270 from Sivantos

Amplivox Ltd, 3800 Parkside, Solihull Parkway, Birmingham Business Park, Birmingham, West Midlands, B37 7YG, United Kingdom

www.amplivox.com | +44 (0)1865 880846 | hello@amplivox.com

# EN-ASS38-V5

For everyone

amplivox

The Amplivox policy is one of continuous development and consequently the equipment may vary in detail from the description and specification in this publication.